

Medium Voltage Switchgear

High Performance High Voltage
Metal-Clad Switchgear



**Powering the Future with
Precision and Control**

EDMP's medium-voltage metal-clad switchgear is a compact, withdrawable indoor solution designed for three-phase AC systems from 3.6kV to 12kV at 50Hz. Ideal for power transmission and distribution in industrial plants, mining operations, utilities, and secondary substations, it supports single bus and sectionalized configurations. It also delivers reliable control, protection, and monitoring for large high-voltage motors and generator outputs.

Compatible with a wide range of circuit breakers—including imported options like VD3, 4AE, HVX, and locally manufactured VSI and WEV series—the switchgear offers full flexibility for various operating environments. It can also be equipped with vacuum contactors and fixed-type load switches.



Energy Storage






Features & Functions

Rated Voltage		<ul style="list-style-type: none"> • 12kV
Rated Current		<ul style="list-style-type: none"> • 630A, 1250A, 1600A, 2000A, 3150A • 2500A / 3150A / 4000A
Rated Frequency		<ul style="list-style-type: none"> • 50Hz
Rated Insulation Level	Lightning Impulse Withstand Voltage (Full Wave)	<ul style="list-style-type: none"> • 75kV (phase-to-phase, phase-to-ground), • 85kV (across breaker gap)
	1-Munite Power Frequency Withstand Voltage	<ul style="list-style-type: none"> • 42kV (phase-to-phase, phase-to-ground), • 85kV (across breaker gap)
	1-Munite Power Frequency Withstand Voltage of Auxiliary Circuit	<ul style="list-style-type: none"> • 2KV
Rated Short-Circuit Breaking Current		<ul style="list-style-type: none"> • 25kA / 31.5kA / 40kA
Rated Short-Time Withstand Current (4s)		<ul style="list-style-type: none"> • 25kA / 31.5kA / 40kA
Rated Peak Withstand Current		<ul style="list-style-type: none"> • 63kA / 80kA / 100kA
Rated Short-Circuit Making Current (peak)		<ul style="list-style-type: none"> • 63kA / 80kA / 100kA
Internal Arc Classification	Circuit Breaker Compartment	
	Busbar Compartment	<ul style="list-style-type: none"> • 40kA / 1s
	Cable Compartment	
Degree of Protection		<ul style="list-style-type: none"> • Enclosure: IP4X • CB Compartment Door Open: IP2X

Operating Conditions

Item	Specification
Ambient Temperature	-10°C ~ +40°C
Max Daily Temperature Variation	Monthly average relative humidity: ≤%90; Daily average relative humidity: ≤%95
Seismic Intensity	≤ Level 8
Atmospheric Conditions	The surrounding air must be free from corrosive, flammable, or explosive gases.

EDMP

 PO Box 125428, Plot No. MO0147C, Junction of N400 & N406 Streets,
 Jebel Ali Free Zone, Dubai, United Arab Emirates
 info@edmpco.com  www.edmpco.com

Copyright © 2026 EDMP Limited. All Rights Reserved. All trademarks are the property of their respective holders. EDMP's Policy is one of continuous product development and the right is reserved to modify specifications contained herein without notice.