

Mk32

ABACUS – Advanced Single Phase Meter

Designed for residential use, **Mk32** is a single phase meter with integrated 100A UC3 compliant relays. It is able to operate in either **STS compliant** prepaid mode or post-paid mode. **Mk32** can operate with A CIU (Customer Interface Unit) – **HD18** or **HD21** wirelessly as a split meter.



Main Functionalities

Standards & Compliance	<ul style="list-style-type: none">• Class 1 and Class 2• IEC 62052-11, 62053-21, 62053-23, 62055-31, 62055-41, 62055-51
-----------------------------------	--

Measurement	<ul style="list-style-type: none">• 1 phase 2 wire (optional neutral current measurement)• 1 phase 3 wire*
--------------------	---

Voltage	<ul style="list-style-type: none">• Nominal voltage: 220V - 240V• Operating range: 0.5Un to 1.2Un• Withstand range: 0V to 456V• Impulse voltage: 4kV
----------------	---

Current	<ul style="list-style-type: none">• WC range: 5/60A, 10/60A, 5/100A,10/100A• WC limit: 30 times I_{max} for 0.5 cycles• Phase current measurement sensor: Shunt• Neutral current measurement sensor: CT
----------------	--

Inputs/Outputs Configuration	<ul style="list-style-type: none">• Up to 5 x LED indicators• Up to 2 x outputs
-------------------------------------	--

Power Consumption	<ul style="list-style-type: none">• Voltage circuit: <10VA/phase, 2W @ V_n• Current circuit: <2.5VA/phase @ I_n
--------------------------	--

Communication Ports	<p>Up to 3 independently working communication ports:</p> <ul style="list-style-type: none">• Optical port: FLAG (IEC 62056-21) <p>Built in Communication</p> <ul style="list-style-type: none">• RF: 300MHz to 950MHz (configurable)• DBPSK PLC Module: 187.5kHz• RS-485 screw terminal (2-wire) <ul style="list-style-type: none">• Pluggable communication module - GPRS/GSM (850/900/1800/1900MHz)
----------------------------	--

Relay	Up to two internal disconnect relays (80A or 120A)
--------------	--

Security	<p>Multi-level security (username and password including encrypted log-in)</p> <ul style="list-style-type: none">• Up to 10 independent security levels• Up to 8 individual users
-----------------	--

Operation Mode	<ul style="list-style-type: none">• Postpaid• Prepaid
-----------------------	--

Battery	<ul style="list-style-type: none">• Internal lithium battery (3.6V)• Internal super capacitor• Backup time: 5 years without power (lithium battery)• Backup time: 48 hours without power (super capacitor)
----------------	---

Protocol	<ul style="list-style-type: none">• EDML command line• DLMS
-----------------	--

Additional Functionalities

Keypad

Option of silicone keypad or capacitive touch keypad
Measured

Measured Values

- 1 element 4 quadrants
- Import/Export/Absolute Wh, varh and VAh
- Per quadrant Wh, varh and VAh
- W, var, VA, Vrms, Irms
- Power factor, frequency

Load Profile

- Up to 8 channels and 2 independent surveys
- Intervals programmable from 1 to 60 minutes
- Energy, instantaneous readings, pulsing inputs as channel sources
- Ability to store average/minimum/maximum values for interval duration

Time of Use

- Up to 8 rates plus unified rate
- Up to 8 separate import and export registers
- Daily, weekly, monthly, yearly and special days
- Up to 48 previous periods plus period totals
- Block or rolling maximum demand
- Time of maximum demand

Tamper Detection and Alarms

- Provision for sealing with conventional wire or plastic seals
- Reverse current detection
- Line and neutral current unbalance detection
- Meter cover and terminal cover detection
- Faulty load relay detection
- Overload detection
- Magnetic tamper detection (optional)
- Alarms are stored in event logs

Software

- Specified operating range: -25°C to +55°C
- Operating range limit: -40°C to +70°C
- Storage range limit: -40°C to +85°C
- Relative humidity: Up to %75 mean, %95 non-condensing for 30 days
- Ingress protection: IP54 (without suction)

Technical Specification

Rated Nominal Voltage	220V - 240V
Operating Voltage Range	0.5Un to 1.2Un
Rated Current & Starting Current	5/60A, 10/60A, 5/100A,10/100A
Rated Frequency	50Hz- 65Hz
Pulse Constant (Configurable)	1000imp/kWh 1000imp/kvarh (Default)
Accuracy Class	Cl.1for Active Cl.2 for Reactive
Battery and Life	Internal Lithium Battery (3.6V) Backup Time: 5 years without battery (lithium Battery)
Data Memory	2 MB of non-volatile memory
Real Time Clock	Precision clock accuracy: <5ppm (15 seconds per month) at 23°C
Specified Operation Range Operating Range Limit	-25°C to +55°C, Humidity is up to 95% -40°C to +70°C Humidity is up to 95%
Terminal	Terminal cross-section: 58.24mm ²
Protection Class	IP54 comply with IEC60529 Insulation grade II

Diagram



EDMP

Design and Product of EDMI Limited

PO Box 125428, Plot No. MO0147C, Junction of N400 & N406
Streets, Jebel Ali Free Zone, Dubai, United Arab Emirates

info@edmpco.com www.edmpco.com

Copyright © 2026 EDMP Limited. All Rights Reserved. All trademarks are the property of their respective holders. EDMP's Policy is one of continuous product development and the right is reserved to modify specifications contained herein without notice.